

Power

ALI Elite Series

Line Interactive UPS
Tower/19" Rack Mount Versions



19" Rack Mount
800 to 2000VA




Tower
600 to 3000VA

- Advanced Buck and Boost Function for Automatic Voltage Regulation
- Surge protected Port for FAX, Modem and Network Equipment
- Hot-Swap battery capability
- Advanced Battery Management (ABM)
- RS-232 Interface to enable monitoring and controlled shut down

The ALI Elite Series is a fully microprocessor controlled, line interactive AVR technology UPS with pure sine wave output providing safe, clean and reliable power to your sensitive electronic equipment. Available in both tower and rackmounted versions with features including fast battery recharge capability, input frequency auto sense and optional external SNMP interface. Typical applications include small servers, work stations, CAD/CAM stations, telephone systems and general office or industrial equipment.

Advanced RS-232 interface combined with AlphaMon complementary software features local utility power and UPS graphical display status, controlled system shut-down, remote administrator alert, utility power quality log and scheduled system shut down/reboot. The ALI Elite Series is fully compliant to international safety and EMC standards and offers a quality cost effective solution to your power needs.



ALI Elite Series

Specifications

Model Tower:	ALI Elite 600	ALI Elite 800	ALI Elite 1000	—	ALI Elite 1500	ALI Elite 2000	ALI Elite 2500	ALI Elite 3000
19" Rack Mount:	—	ALI Elite 800RM	—	ALI Elite 1250 RM	ALI Elite 1500 RM	ALI Elite 2000 RM	—	—
Input								
Capacity:	600VA/ 360W	800VA/ 480W	1000VA/ 600W	1250VA/ 750W	1500VA/ 900W	2000VA/ 1200W	2500VA/ 1500W	3000VA/ 1800W
Battery								
DC Voltage:	24V	24V	24V	24V	36V	48V	48V	48V
Backup Time								
80% Load:	11	7	5	10	4	5	6	8
50% Load:	20	14	10	21	9	10	12	15
Dimensions								
Tower								
WxDxH (mm):	140 x 436 x 210	140 x 436 x 210	140 x 436 x 210	—	170 x 450 x 226	170 x 450 x 226	170 x 450 x 226	(2x) 170 x 450 x 226
19" Rackmount								
WxDxH (mm):	—	483 x 381 x 130	—	483 x 381 x 130	483 x 381 x 130	483 x 381 x 130	—	—
Weight								
Tower (kg):	13.8	14.5	15.0	—	25.0	30.0	30.0	20.2 + 25.4
19" Rack Mount:	—	18.0	—	23.5	26.1	28.4	—	—
Environment								
Audible Noise:	<40dB(A) (at 1m)	<40dB(A) (at 1m)	<40dB(A) (at 1m)	<40dB(A) (at 1m)	<40dB(A) (at 1m)	<40dB(A) (at 1m)	<40dB(A) (at 1m)	<40dB(A) (at 1m)

Technical Specifications

Input

Voltage: 220V/230V/240V nominal selectable
 Voltage Range: $\pm 25\%$ at nominal line input, single phase
 Frequency: 50Hz or 60Hz, $\pm 5\text{Hz}$ (auto sensing)
 Unit Input Protection: Fuse or breaker

Output

Frequency (on battery): 50Hz or 60Hz, $\pm 0.5\%$
 Voltage (on battery): Pure sine wave at $\pm 5\%$ of nominal, -10% of nominal after low battery warning
 Voltage Regulation (AVR): AVR automatically increase output voltage 15% above input voltage if line voltage is -9 to -25% of nominal
 AVR decrease output voltage 15% below input voltage if line voltage is 9 to 25% of nominal

Filtering & Protection

Spike Protection: 320Joules, 2ms
 Overload Protection: Automatic shutdown if overload exceeds 110% of nominal at 20sec and 125% at 2sec
 Transfer Time: 2 to 4ms (typical) including detection time
 Short Circuit: UPS output cut off immediately or input fuse (or breaker) protection

Battery

Type: Hot swappable, sealed, maintenance free lead acid, with 3 to 5 years lifetime
 Protection: Automatic self-test and deep discharge protection, replace battery indicator
 Typical Recharge Time: 4hrs (to 90% of full capacity)

Alarm

Battery Backup: Slow beeping sound (about 0.25Hz)
 Battery Low: Rapid beeping sound (about 1.00Hz)
 Overload: Continuous beeping sound

Interface

RS-232: Bi-directional communication port (optional SNMP network adaptor)
 LED Indicators: Overload, Backup, Replace Battery, Buck AVR, Line Normal, Boost AVR, Load Bar Graph, Power Bar Graph

Environment

Operation Conditions: 3,500m max. altitude, 0 to 95% humidity non-condensing, 0 to 40°C ambient temperature
 Storage Condition: 15,000m max. altitude, 0 to 95 % humidity non-condensing, -15 to 48°C ambient temperature
 Certification: Safety (EN 50091-1, EN 60950), EMC (EN 50091-2, EN50022/B, CISPR 22)

Warranty

24 Months

For contact information visit www.alpha.com

The Alpha Group >	Europe, Middle East & Africa	Asia Pacific	North America	Latin & South America
	Cyprus Tel: +357 25 375 675 Fax: +357 25 359 595 Russia Tel: +7 495 916 1854 Fax: +7 495 916 1349	Germany Tel: +49 9122 79889 0 Fax: +49 9122 79889 21 Lithuania Tel: +350 5 210 5291 Fax: +350 5 210 5292 United Kingdom Tel: +44 1279 501110 Fax: +44 1279 659870	P.R. China Tel: +852 2736 8663 Fax: +852 2199 7988	Canada Tel: +1 604 430 1476 Fax: +1 604 430 8908 USA Tel: +1 360 647 2360 Fax: +1 360 671 4936
	Contact USA office			